STATUS: Standard

CLASSIFICATION OF EQUIPMENT : Unclassified

USING SERVICE: Army


DATE OF THIS SHEET: 12 Feb 52

AN/PGC-TYPE

AN/COMP TYPE NUMBER:

TT-61/FG

TELETYPEWRITER



Teletypewriter TT-61/FG is a transportable, page-printing, standard communication, sending and receiving teletypewriter station equipment used at permanent or semipermanent camps, posts, and stations.

This equipment consists essentially of tactical Teletypewriter TT-4/TG adapted to fixed plant applications. It includes an operating table which contains an adapter unit and a power supply.

It is primarily intended for neutral sending and neutral or polar receiving and can operate on a 60-ma d-c line or a 20-ma d-c v-f facility.

Can be operated on 95/125 v or 190/250 v ac supplied by the power supply component.

TT-61/FG

TELETYPEWRITER

:AN/COMP TYPE NUMBER USING SERVICE : Army

INSTRUCTION LITERATURE: TM 11-2236 CLASSIFICATION OF EQUIPMENT: Unclassified

DATE OF THIS SHEET: 12 Feb 52

MAJOR COMPONENTS

QUANT	NAME OF COMPONENT	DIMENSIONS (IN) INSTALLED	WEIGHT (LBS)
gueroo	Teletypewriter TT-4/TG	24-3/8 × 20-7/8 × 16-3/8	94.50
ge of	Power Supply PP-604/FG	12 × 8-7/8 × 7-1/8	29.25
gossa	Teletypewriter Table FN-45/FG	18-5/8 × 21-1/4 × 27	24.75

OPERATIONAL CHARACTERISTICS

TACTICAL USE: Posts, camps, stations, depots.

INSTALLATION: Fixed or semifixed station.

CAN COMMUNICATE WITH: Terminal, repeater, or station apparatus over wire, cable, carrier, or

radioteletype standard communication facilities composing the system

in which it operates.

TECHNICAL CHARACTERISTICS

OPERATING FUNCTIONS: Remote motor stop, break-in key, bell, carriage return, line feed,

space-repeat.

OPERATING SPEED: 368.1 opm convertible to 404 opm or 600 opm.

MOTOR CHARACTERISTICS: Universal, series-governed motor; 3,600 rpm. 150 w, 115 v, 50 to 60

cyc, one phase, ac or 150 w, 115 v dc.

POWER REQUIREMENTS: For Power Supply PP-604/FG, 95-125 v or 190-250 v ac, 25 to 60 cyc,

single phase, maximum demand 45 w with no a-c load.

PHYSICAL CHARACTERISTICS

Teletypewriter TT-61/FG weighs 99.5 pounds net, volume 11.03 cu ft. Packed for domestic or export shipment: total weight 260 pounds, total volume 23.7 cu ft. Shipped in 3 packages.

CONFIDENTIAL—Security Information

ORIGINAL